

DENNISON MFG IDENTIFICATION SYSTEMS DIV -- CARTER'S RUBBER
CEMENT THINNER
MATERIAL SAFETY DATA SHEET
FSC: 6850
NIIN: 00N001133
Manufacturer's CAGE: 16956
Part No. Indicator: A
Part Number/Trade Name: CARTER'S RUBBER CEMENT THINNER

=====
=====
General Information
=====

=====
Company's Name: DENNISON MFG CO IDENTIFICATION SYSTEMS DIV *
Company's Street: 300 HOWARD STREET *
Company's City: FRAMINGHAM *
Company's State: MA *
Company's Country: US *
Company's Zip Code: 01701-8832 *
Company's Emerg Ph #: 508-879-0511 *
Company's Info Ph #: 508-879-0511 *
Safety Data Action Code: C
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 001
Date MSDS Prepared: 19JUL88
Safety Data Review Date: 20SEP95 *
MSDS Serial Number: BCHCK
Hazard Characteristic Code: F3 *
NRC/State License Number: N/A
Net Propellant Weight-Ammo: N/A
=====

=====
=====
Ingredients/Identity Information
=====

=====
Proprietary: NO
Ingredient: NAPHTHENE
Ingredient Sequence Number: 01
Percent: 10.0
NIOSH (RTECS) Number: 1000794NA

Proprietary: NO
Ingredient: PARAFFINIC SOLVENT
Ingredient Sequence Number: 02
Percent: 90.0
NIOSH (RTECS) Number: 1000088PS

=====
=====
Physical/Chemical Characteristics
=====

=====
=====
Appearance And Odor: WATER-WHITE LIQUID W/HYDROCARBON ODOR.
Boiling Point: >151F,>66C
Melting Point: N/A
Vapor Pressure (MM Hg/70 F): 250
Vapor Density (Air=1): 3.3
Specific Gravity: 0.72 (H*2O=1)
Evaporation Rate And Ref: 5.8 (BUTYL ACETATE=1)
Solubility In Water: NEGLIGIBLE
=====

=====
=====
Fire and Explosion Hazard Data
=====

=====
=====
Flash Point: <10F,<-12C
Flash Point Method: TCC
Lower Explosive Limit: 1.1%
Upper Explosive Limit: 7%
Extinguishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER FOG
OR
SPRAY.
Special Fire Fighting Proc: WEAR NIOSH/MSHA APPROVED SCBA & FULL
PROTECTIVE EQUIPMENT (FP N). COOL EXPOSED CONTAINERS W/WATER
SPRAY.
Unusual Fire And Expl Hazrds: IN CASE OF LARGE FIRES, ALSO COOL
SURROUNDING EQUIPMENT & STRUCTURES W/WATER. DO NOT STORE OR
MIX W/STRONG
OXIDANTS.
=====

=====
=====
Reactivity Data
=====

=====
=====
Stability: YES
Cond To Avoid (Stability): HEAT, SPARKS & OPEN FLAMES.
Materials To Avoid: STRONG OXIDIANT SUCH AS CHLORINE.
Hazardous Poly Occur: NO
=====

=====
=====
Health Hazard Data
=====

Signs/Symptoms Of Overexp: EYE IRRIT, DRYING OF SKIN, EXCESS INHAL CAUSES HEADACHE, DIZZINESS AND NAUSEA.
Emergency/First Aid Proc: EYE CONTACT:FLUSH W/WATER; SKIN CONTACT: WASH W/MILD SOAP & WATER & APPLY SKIN CREAM; INHALATION: REMOVE TO FRESH AIR & CALL PHYSICIAN; APPLY ARTIFICIAL RESPIRATION IF NECESSARY.

=====
=====
Precautions for Safe Handling and Use
=====

Steps If Matl Released/Spill: FLUSH W/WATER INTO RETAINING AREA OR CONTAINER. AVOID EXPOSURE TO SPARKS, FIRE OR HOT METAL SURFACES. (MFR RECM)
Waste Disposal Method: INCINERATE UNDER SAFE CONDITIONS. MUST BE IAW LOCAL,STATE, & FEDERAL CODES.
Precautions-Handling/Storing: KEEP AWAY FROM HEAT, SPARKS, & OPEN FLAME.
USE W/ ADEQUATE VENTILATION. AVOID PROLONG OR REPEAT CONTACT W/ SKIN. REFER TO CONTAINER LABEL. (MFR RECM).

=====
=====
Control Measures
=====

Respiratory Protection: SELF-CONTAINED BREATHING APPARATUS FOR CONC > TLV (NIOSH/MSHA APPRD)
Ventilation: LOCAL(OR MECH EXHAUST: CLASS D EXPLO PROOF MOTOR & SWITCHES)
Protective Gloves: REQUIRED
Eye Protection: REQUIRED
Other Protective Equipment: EYE BATH & SAFETY SHOWER
Suppl. Safety & Health Data: COMBINED TLV FOR NAPHTHENE & PARAFFINIC SOLVENT IS 160 PPM (MFR RECM). VAPOR MEAS AT 69F.

=====
=====
Transportation Data
=====

Trans Data Review Date: 83068
DOT PSN Code: GJJ
DOT Proper Shipping Name: FLAMMABLE LIQUIDS, N.O.S.

DOT Class: 3
DOT ID Number: UN1993
DOT Pack Group: II
DOT Label: FLAMMABLE LIQUID
IMO PSN Code: HIN
IMO Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. *
IMO Regulations Page Number: 3230
IMO UN Number: 1993
IMO UN Class: 3.2
IATA PSN Code: MBV
IATA UN ID Number: 1993
IATA Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. * *
IATA UN Class: 3
IATA Label: FLAMMABLE LIQUID
AFI PSN Code: MBV
AFI Prop. Shipping Name: FLAMMABLE LIQUIDS, N.O.S. *
AFI Class: 3
AFI ID Number: UN1993
AFI Pack Group: II
AFI Label: FLAMMABLE LIQUID
AFI Basic Pac Ref: 7-7

=====
=====
Disposal Data
=====

=====
=====
Disposal Data Review Date: 89242
Rec # For This Disp Entry: 01
Tot Disp Entries Per NSN: 001
Landfill Ban Item: YES
Disposal Supplemental Data: COMBINED TLV FOR NAPHTHENE & PARAFFINIC
SOLVENT IS 160 PPM (MFR RECM). VAPOR MEAS AT 69F. IN CASE OF
ACCIDENTAL
EXPOSURE OR DISCHARGE, CONSULT HEALTH AND SAFETY FILE FOR
PRECAUTIONS.
1st EPA Haz Wst Code New: D001
1st EPA Haz Wst Name New: IGNITIBLE
1st EPA Haz Wst Char New: IGNITABILITY
1st EPA Acute Hazard New: NO

=====
=====
Label Data
=====

=====
=====
Label Required: YES
Technical Review Date: 08APR94

Label Status: G
Chronic Hazard: NO
Signal Word: DANGER!
Acute Health Hazard-Moderate: X
Contact Hazard-Slight: X
Fire Hazard-Severe: X
Reactivity Hazard-None: X
Special Hazard Precautions: FLAMMABLE. AVOID OXIDIZERS. ACUTE: MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION, HEADACHES, DIZZINESS, NAUSEA AND UNCONSCIOUSNESS. CHRONIC: NONE LISTED BY MANUFACTURER.
Protect Eye: Y
Protect Skin: Y
Protect Respiratory: Y
Label Name: DENNISON MANUFACTURING CO, STATIONARY PRODUCTS
Label Street: 300 HOWARD STREET
Label City: FRAMINGHAM
Label State: MA
Label Zip Code: 01701
Label Country: US
Label Emergency Number: 508-879-0511 X 4636

=====
=====

URL for this msds <http://hazard.com>. If you wish to change, add to, or delete information in this archive please sent updates to dan@hazard.com.