



BlueDEF Diesel Exhaust Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 10/01/2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : BlueDEF Diesel Exhaust Fluid

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Solution for NOx reduction in SCR systems

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC
3100 Sanders Road
Northbrook, IL 60062 - USA
T (847) 559-2000
www.oldworldind.com

1.4. Emergency telephone number

Emergency number : 800 424 9300 (United States); 00 1 703 527 3887 (International)
Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :
Signal word (GHS-US) : None
Hazard statements (GHS-US) : None
Precautionary statements (GHS-US) : None

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% by wt	GHS-US classification
water	(CAS-No.) 7732-18-5	67.5	Not classified
urea	(CAS-No.) 57-13-6	32.5	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

BlueDEF Diesel Exhaust Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- | | |
|--------------------------------------|---|
| First-aid measures after eye contact | : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. |
| First-aid measures after ingestion | : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. |

4.2. Most important symptoms and effects, both acute and delayed

- | | |
|------------------|--|
| Symptoms/effects | : Not expected to present a significant hazard under anticipated conditions of normal use. |
|------------------|--|

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- | | |
|--------------------------------|---|
| Suitable extinguishing media | : Foam. Dry powder. Carbon dioxide. Sand. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Special hazards arising from the substance or mixture

- | | |
|------------|--|
| Reactivity | : No dangerous reactions known under normal conditions of use. |
|------------|--|

5.3. Special protective equipment and precautions for fire-fighters

- | | |
|--------------------------------|---|
| Firefighting instructions | : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|------------------|--|
| General measures | : The EPA has no established reportable quantity for spills for this material, secondary containment is not specified. |
|------------------|--|

6.1.1. For non-emergency personnel

- | | |
|----------------------|-----------------------------------|
| Emergency procedures | : Evacuate unnecessary personnel. |
|----------------------|-----------------------------------|

6.1.2. For emergency responders

- | | |
|----------------------|--|
| Protective equipment | : Equip cleanup crew with proper protection. |
| Emergency procedures | : Ventilate area. |

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|---|
| Methods for cleaning up | : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. For minor spillages wash down with excess of water. Mop up small spills. |
|-------------------------|---|

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|---|
| Precautions for safe handling | : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. |
|-------------------------------|---|

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|------------------------|--|
| Storage conditions | : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Keep container closed when not in use. |
| Incompatible materials | : Strong acids. Strong bases. |

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

BlueDEF Diesel Exhaust Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

urea (57-13-6)

Not applicable

water (7732-18-5)

Not applicable

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Gloves. Protective goggles.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

Wear appropriate mask



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless
Odor	: characteristic ammonia odor
Odor threshold	: No data available
pH	: 9 - 10
Relative evaporation rate (butylacetate=1)	: < 1
Freezing point	: -11 °C (12 °F)
Boiling point	: > 100 °C (212 °F)
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: Not Applicable
Relative vapor density at 20 °C	: 0.6 H ₂ O, >1
Specific Gravity	: 1.09
Solubility	: Soluble in water. Water: 100 %
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

BlueDEF Diesel Exhaust Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Not established.

10.5. Incompatible materials

Strong acids. Strong bases. oxidizing agents (peroxides, chromates, dichromates).

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Fume.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

urea (57-13-6)	
LD50 oral rat	14300 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male, Experimental value)
ATE US (oral)	14300 mg/kg bodyweight

Skin corrosion/irritation : Not classified
pH: 9 - 10

Serious eye damage/irritation : Not classified
pH: 9 - 10

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

SECTION 12: Ecological information

12.1. Toxicity

urea (57-13-6)	
LC50 fish 1	> 6,810.00 mg/l (96 h, Leuciscus idus, Experimental value, Nominal concentration)
EC50 Daphnia 1	> 10,000.00 mg/l (DIN 38412-11, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

urea (57-13-6)	
Persistence and degradability	Readily biodegradable in water.
ThOD	0.27 g O ₂ /g substance

BlueDEF Diesel Exhaust Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

urea (57-13-6)	
BCF fish 1	1.00 (72 h, Brachydanio rerio, Fresh water, Literature study)
Log Pow	< -1.73 (Experimental value, EU Method A.8: Partition Coefficient)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

urea (57-13-6)	
Mobility in soil	Not applicable
Log Koc	-1.43 - -1.19 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Effect on the ozone layer : No additional information available

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : As a non-hazardous liquid waste, it should be solidified with stabilizing agents such as sand, fly ash, or clay absorbent, so that no free liquid remains before disposal to an industrial waste landfill.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Refer to current TDG Canada for further Canadian regulations

ADR

Not regulated

Transport by sea

In accordance with IMDG / IMO

Not regulated

Air transport

In accordance with IATA / ICAO

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

BlueDEF Diesel Exhaust Fluid

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BlueDEF Diesel Exhaust Fluid	
EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed
CERCLA RQ	None. This material is not classified as hazardous under U.S. EPA regulations.
SARA Section 302 Threshold Planning Quantity (TPQ)	No extremely hazardous substances are in this product.
SARA Section 311/312 Hazard Classes	Urea. No hazards resulting from the material as supplied.
urea (57-13-6)	
EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed
water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

BlueDEF Diesel Exhaust Fluid	
WHMIS Classification	This SDS has been prepared according to the criteria of the Hazardous Products Regulations (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR. Applicable GHS information is listed in section 2.2 of this SDS.

15.3. US State regulations

California Proposition 65 - This product does not contain any substance(s) known to the state of California to cause cancer, developmental toxicity and/or reproductive toxicity

SECTION 16: Other information


Revision date : 10/01/2019

Full text of H-statements:

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



SDS GHS US (GHS HazCom 2012) OWI

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.