MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

	iodilon Clandard 20 Of It 10		10 001 1/ (1 011	11 11 7		
	IDENTITY AND DISTRIBUTOR'S INFORMATION					
NFPA Rating: Health-2; Flammability-1; Reactivity-0; Special-0	HMIS Rating: Health-2; Flammability-1; Reactivity-0; Personal Protection-B					
Manufactured For: WAXIE Sanitary Supply Address: 9353 Waxie Way	DOT Hazard Classification: ORM-D					
Address: San Diego, CA 92193-1036	Identity (trade name as used on label):					
Phone: 1-800-995-4466	Waxie Edge Off Baseboard Cleaner & Wax Stripper					
	MSDS Number: 807 Revision- 12					
	Date Prepared: 06/19/02 Prepared By: CH/IB Information Calls: 858-292-8111					
SECTION 1 - MATERIAL IDE						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	O/10 (Yamber	III LIST	(ppm)	TLV (ppm)	Ref. Source **	
MONOETHANOLAMINE	141-43-5	No	3	3	d	
ISOBUTANE	75-28-5	No	800	800	d	
2-BUTOXYETHANOL *	111-76-2	Yes	25	20	d	
*GLYCOL ETHER			(skin)	(skin)		
				<u> </u>		
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -						
<u> </u>						
	or Density (Air = 1): N/E Evaporation Rate (= 1): N/E					
Appearance and Odor: Gelled spray with mint and amine fragrance.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA FLAMMABILITY as per USA FLAME PROJECTION TEST Auto Ignition Temperature Flammability Limits in Air by % in Volume:						
(aerosols) NON-FLAMMABLE	N/E					
erosols) NON-FLAMMABLE N/E % LEL: N/E % UEL: N/E ASH POINT AND METHOD USED (non-aerosols): N/A EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.						
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR						
Incompatibility (Mat. to avoid): Strong organic acids, strong mineral Conditions to Avoid: Open flame, welding arcs, heat.						
acids, alkaline metals and copper.						
Hazardous Decomposition Products: CO, CO2, nitrogen compounds.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS						
ACUTE EFFECTS						
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.						
Eye Contact: Irritation Skin Contact: Irritation						
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.						
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause nasal & respiratory irritation, diarrhea,						
vomiting. Lab animals have experienced anemia, liver, kidney, lung, and blood damage due to 2-butoxyethanol.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for 15 minutes, followed by a 1% saline solution. If irritated, seek medical attention.						
Skin Contact: Wash with soap and water. If irritated, seek medical attention.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.						
ngestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH for organic vapors.						
Protective Gloves: Rubber gloves recommended. Eye Protection: Safety glasses recommended.						
/entilation Requirements: Adequate ventilation to keep vapor concentra	ition below TLV.	·				
Other Protective Clothing & Equipment: None						
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal						
egulations. Flush small spills to sewer.						
Vaste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors						